

SURFACE PREPARATION

Surface must be clean, dry and free of any foreign matter. Smooth surfaces and new paint should be sanded, primed or acid etched before application. For best results, clean application surface with a de-greaser followed by rinsing with water. All rust should be treated prior to application. Surface must be dry before proceeding. Do not apply directly to uncoated steel as rust & corrosion may occur.

MATERIAL PREPARATION

This product is ready to use out of the bucket with no secondary additive required. To thin, use no more than 15% added water.

APPLICATION

Some settling may occur so mix entire contents of bucket prior to use. Second Skin Bed Liner is best when brushed, but may also be applied with a roller or an undercoating gun with a 2mm tip. When brushing the product, use crisscross brushstrokes to ensure even coverage. Use only with adequate ventilation. Do not breathe vapors, spray mists or sanding dust.

CLEAN UP

Clean up equipment, tools and spills promptly with warm soapy water.

COVERAGE & DRY TIME

One gallon will cover approximately 25 square feet at 1/8 inch. Dries to touch in 4-6 hours. Cures in approximately 48- 72 hours depending on temperature and humidity. It is highly recommended that nothing be hauled in the truck bed until 4 days has passed since the last coat.



DIY BEDLINER

A single system acrylic & urethane blend designed to protect and beautify the ugliest of truck beds.

WARRANTY

This product has been formulated with the utmost concern for successful results. Since application and existing conditions may vary, the customer or final user must determine the suitability of the product for the intended use and assume all liabilities, direct and indirect or consequential damage.

FIRST AID

RESPIRATORY – If you experience breathing distress, leave area and obtain fresh air.

EYE – In case of eye contact, flush with large amounts of fresh water for 15 minutes. Seek medical attention.

SKIN – In case of skin contact, wash affected area with soap and water. Remove soiled clothing. Seek medical attention if irritation persists. Wash clothing before reuse.

INGESTION – If swallowed DO NOT INDUCE VOMITING. Seek Medical attention immediately.

May cause eye, skin, nose, and throat irritation. If indoors, open windows and doors to ensure continuous flow of fresh air during mixing, application and drying and sanding. When spraying, or in the event you experience eye irritation, increase air flow or wear respiratory protection, or leave area. If adequate ventilation cannot be provided, wear an approved respirator (TC21C or equivalent). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Use safety eyewear with splash guards.

KEEP OUT OF REACH OF CHILDREN

LOW VOC. Contains less than 125 grams per liter VOC

NOTICE! Do not apply if surface or air temperature is below 50°, or if rain is expected before dry time. Damp or humid conditions will slow dry time. KEEP FROM FREEZING