second skin AUDIO

Acoustic Pro™ Fabric Wrapped Panels

ANCHORAGE FABRIC SPECS

- 100% Recycled & Recyclable
- Woven in North America
- ASTM E84 Class I or A
- UL Panel Fabric Recognized
- Acoustically Transparent
- Tested for Colorfastness



Fabric:	Anchorage 2335 (Guilford of Maine)
Content:	100% post-consumer recycled polyester
Weight:	2335 - 15.2 ± 1.0 oz./lin. yd
Width:	2335 - 66" min. useable
Repeat:	None | The pattern does not repeat, so no pattern matching is needed
Strength:	Breaking 275 lbf min. (warp and fill; ASTM D5034)
Light Fastness:	Grade 4 min. at 40 hours (AATCC 16.3 Option 3)
Crocking:	Grade 4 min. dry, Grade 3 min. wet (AATCC 8)
Flammability:	ASTM E84 Class I or A
Sustainability:	100% recycled and recyclable
Acoustic Transparency:	85% | For more detailed results, please reach out.
Cleaning:	Standard Care Label W-S. Clean with water based cleaning agents, foam, or pure, water free solvents. Vacuum or lightly brush to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quat based cleaners.