second skin AUDIO

# Acoustic Pro™ Fabric Wrapped Panels

## FR701 FABRIC SPECS

- 100% Recycled Polyester
- Woven in North America
- ASTM E84 Class I or A
- UL Panel Fabric Recognized
- Acoustically Transparent
- Non-Directional Fabric



| | |
|---|---|
| **Fabric:** | FR701® 2100 (Guilford of Maine) |
| **Contents:** | 100% post-consumer recycled polyester |
| **Weight:** | 16.0 ± 0.5 oz./lin. yd. |
| **Width:** | 66" min. useable |
| **Repeat:** | None \| The pattern does not repeat, so no pattern matching is needed |
| **Treatment:** | None \| No finish or coating has been added to the fabric |
| **Backing:** | None \| No layer is attached to the back of the fabric |
| **Strength:** | Breaking 150 lbf min. \| Tear 30 lbf min. (warp and fill; ASTM D5034, ASTM D2261) |
| **Light Fastness:** | Grade 4 min. at 40 hours (AATCC 16.3 Option 3) |
| **Crocking:** | Grade 4 min. dry, Grade 3 min. wet (AATCC 8) |
| **Flammability:** | ASTM E84 Class I or A |
| **Sustainability:** | 100% recycled and recyclable |
| **Acoustic Transparency:** | 95% \| For more detailed results, please reach out. |
| **Cleaning:** | Standard Care Label W-S. Clean with water based cleaning agents, foam, or pure, water free solvents. Vacuum or lightly brush to prevent dust and soil buildup. May be cleaned with a 10% bleach-to-water solution; rinse well. May also be disinfected with hydrogen peroxide, alcohol, and quat based cleaners. |