

Luxury Liner™ E84 Class A MLV

SPEC SHEET

- ✓ **Class A Fire Rated Sound Barrier**
- ✓ **Reinforced with Polyester Scrim for Extra Strength**
- ✓ **UV Resistant with Extended Resistance Available**
- ✓ **Flexible and Durable**



Material:	Mass Loaded Vinyl Reinforced with Polyester Scrim
Patterns:	Smooth Vinyl
Features:	Class A Fire Rated, Blocks Airborne Noise, STC 26, UV Resistant with Extended UV Resistance Available, High Tear Strength and Breaking Strength, Custom Facings (Fabric/Films/Prints) Available for Large Projects, Paintable, Flexible, Durable
Application:	Sound Stages, Outdoor Venue Barriers, Fire Rated Barrier, Generator Boxes and Enclosures, Mechanical Rooms, Divider Wall, Construction Sites, Event Tent Walls
Dimensions:	4.5' x 10' (45 Sq Ft) & 4.5' x 20' (90 Sq Ft)
Thickness:	Nominal 1/8"
Weight:	1.00 lbs per sq ft
Strength Testing: ASTM D751	Elongation: 15% Breaking Strength: 300 lbs Tear Strength: 30 lbs
Fire Rating:	NFPA 701 SS; UL 94 V-O; CAN ULCS102; ASTM E84 Class A Flame Spread: 5 Smoke Developed: 150
Color:	Off-White
Installation:	Staples, Screws (with Washers), Nails, or Hung with Reinforced Grommets

Sound Transmission Loss

Product	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	STC
Luxury Liner™ E84 Class A MLV	16	17	22	27	32	37	26

