second skin
auto & home insulation

SECONDSKINAUDIO.COM
1.800.679.8511
SERVICE@SECONDSKINAUDIO.COM

PolyZorbe™ Acoustic Panels

SPEC SHEET

- Architecturally Decorative
- Controls Echo & Reverb
- No Formaldehyde
- No Chemical Irritants
- Class A Fire Rated
- Custom Graphics

Material:	Polyester (60% Recycled)
Patterns:	Fibrous, Semi-Rigid
Features:	Decorative, Lightweight, Tackable Surface, Non-Toxic, Non-Allergenic, Fungal Resistant
Application:	Offices, Conference Rooms, Homes, Recording Studios, Schools, Airports, Bars, Restaurants, Music Rooms, Universities, Hospitals, Medical Clinics, Houses of Worship, Theaters, Multi-Purpose Rooms, Government & Municipal Facilities
Thickness:	1/2", 1", & 2"
Sizes:	24” x 48”, Custom Sizes Available up to 48” x 96”
Color (1" & 2"):	Beige, Black, Silver, White
Color (1/2"):	Beige, Black, Blue, Brown, Green, Grey, Orange, Purple, Red, Silver, Tan, White
Light Reflectance:	1/2" White: 87 | 1" White: 83 | 2" White: 82
Flammability:	ASTM E84, Class A | Flame Spread: 15 | Smoke Developed: 250
Installation:	Acoustical Adhesive

Noise Reduction Coefficient

Size	Test Mount	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1/2" PolyZorbe™ Panel	A-Mount (Wall Mount)	0.01	0.07	0.26	0.54	0.78	0.94	0.40
1" PolyZorbe™ Panel	A-Mount (Wall Mount)	0.08	0.20	0.59	0.94	1.04	1.02	0.70
2" PolyZorbe™ Panel	A-Mount (Wall Mount)	0.31	0.58	1.08	1.11	1.04	1.04	0.95

Color Options

Orange

Brown

Red

Grey

Black

Silver

Beige

Tan

White

Blue

Purple

Green



second skin auto & home insulation

TO ORDER THIS PRODUCT VISIT:

PolyZorbe™ Acoustic Panel (1" or 2")

PolyZorbe™ Vivid Acoustic Panel (All Colors) (1/2")

Find us in MasterSpec® Powered by Deltek Specpoint®