

Timberwool™ Ceiling Tiles

SPEC SHEET

- ✓ EZ Drop Lay In Tiles
- ✓ Controls Echo & Reverb
- ✓ Eco-Friendly Wood Fiber
- ✓ Primed and Ready to Paint
- ✓ Engravable for Design Flexibility
- ✓ Class A Fire Rated

**CUT AND PAINT LIKE WOOD!**

Material:	Wood Fibers, Portland Cement, Water
Patterns:	Cementitious Wood Wool Fibers
Features:	EZ Drop, Decorative, Cut and Paint like Wood, Cost-Effective, Fire Resistant, Manufactured from Natural Products
Application:	Offices, Conference Rooms, Manufacturing Facilities, Schools, Airports, Bars, Restaurants, Music Rooms, Universities, Hospitals, Medical Clinics, Houses of Worship, Theaters, Multi-Purpose Rooms, Government Facilities, Shooting Ranges
Thickness:	5/8" & 1"
Sizes:	23.75" x 23.75" & 23.75" x 47.75", Cuttable to Any Size
Weight:	23.75" x 47.75" x 5/8" - 10 lbs, 23.75" x 47.75" x 1" - 16 lbs
Color:	Primed Clear & Primed White (ready to be painted)
Light Reflectance:	Primed White: 70
Flammability:	ASTM E84, Class A Flame Spread: 10 Smoke Developed: 0
Installation:	Lay In

Noise Reduction Coefficient

Size	Test Mount	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
5/8" Timberwool™ Ceiling Tile	E-400 (no backer)	0.72	0.51	0.37	0.50	0.62	0.74	0.50

